

MT-1034-SC/APC- SC/APC Fiber Optic Patch Cord



(SC/APC patch cord)

Quick Details:

01. Product Name : SC/APC Fiber optic patch cord (pigtailed)
02. Place of Origin : China
03. Model No : MT- 1034-SC/APC- SC/APC
04. Connector type: SC, FC, ST, LC, MT-RJ, E2000, ESCON,DSC, MPO
05. Polish type: PC, UPC, APC can be chosen
06. Mode type: Single-mode or Multimode
07. Material of the jacket: LSZH or PVC
08. Fiber type: G652D, G657A1, G657A2 can be chosen
09. Diameter of cable: 0.9mm, 2.0mm, 3.0mm can be chosen
10. Length of cable: as you wish
11. Application: FTTX, Data Center, Network cabling.etc

Description:

SC-ST, ST-ST,LC-ST,MTRJ-ST,FC-ST, **50/125 62.5/125 Multimode Duplex Patch cord**

9/125 Single-mode Duplex Patch cord

Patch Cable, Patch cord type

available: FC-FC,SC-SC,SC-ST,ST-ST,LC-LC,LC-SC,LC-ST,MTRJ-ST,MTRJ-SC,MTRJ-MTRJ,MTRJ-LC,FC-F
C,FC-ST,FC-SC,FC-LC,FC-MTRJ

50/125 Multimode Duplex Patch cord

Patch Cable, Patch cord type

available:SC-SC,SC-ST,ST-ST,LC-LC,LC-SC,LC-ST,MTRJ-MTRJ,MTRJ-SC,MTRJ-ST,MTRJ-LC,FC-FC,FC-SC,
FC-ST,FC-LC,FC-MTRJ

62.5/125 Multimode Duplex Patch cord

Patch Cable, Patch cord type

available: SC-ST,ST-ST,LC-LC,LC-SC,LC-ST,MTRJ-MTRJ,MTRJ-SC,MTRJ-ST,MTRJ-LC,FC-FC,FC-SC,FC-ST,FC-LC,FC-MTRJ,SC-SC

Parameter:

Type	Single-mode/UPC	Single-mode/APC	Multimode/PC
Insertion loss	≤0.3 dB	≤0.3 dB	≤0.3 dB
Return loss	≥50dB	≥60dB	≥35dB
Exchangeability	≤0.2 dB	≤0.2 dB	≤0.2 dB
Operation temperature	-40°C to +80°C	-40°C to +80°C	-40°C to +80°C
Insertion time	1000	1000	1000

The difference of different cable diameters:



You may interested in:

